

WHEELS

Product group	Wheels
Item number	59696063
Valid wheel size	16 x 6.50 - 8
Brand	Deli
Tread pattern	S-317
LI / SI / PR	72 A6, 6 PR
TL/TT	тт
Hub design	End cap assembly
Type of bearing	Ball bearing
Shaft diameter [mm].	25
Mounting length [mm]	64
Hub length [mm]	73
Rim colour	Silver
Load capacity complete wheel [kg]	355
Speed complete wheel [km/h]	16



Technical Informations

Assembly Item no. Tyres	19110128
LI / SI / PR	72 A6, 6 PR
TL/TT	тт
Brand	Deli
Tread pattern	S-317
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Maximum air pressure [bar]. 2,90 Section width (mm) 168 Stat. radius (SLR) [mm] 188 Rolling circumference [mm]. 1230 Tread depth (mm) 2,0 Assembly Item no. Rim • 39600052	
Stat. radius (SLR) [mm] 188 Rolling circumference [mm]. 1230 Tread depth (mm) 2,0	
Rolling circumference [mm]. 1230 Tread depth (mm) 2,0	
Tread depth (mm) 2,0	
Assembly Item no. Rim • 39600052	
Valid rim size 5.50 A x 8 H2	
Load capacity of rim 1 [kg] 700	
Speed Rims 1 [km/h] 16	
Maximum speed [km/h]. 16	
Type of drive Towed axle	
Hump H2	
Single / multi-part einteilig	
Rim material steel	
RAL RAL9006	
Number of drain holes 3	
Verschweißung beidseitig No	
Offset hub Yes	
Additional socket required No	
Valve seat External Valve	
Valve hole diameter [mm] 11.3	
Valve designation TR 13	