

WHEELS

| Product group | Wheels |
|-----------------------------------|-----------------|
| Item number | 59696095 |
| Valid wheel size | 3.00 - 4 |
| Brand | Starco |
| Tread pattern | ST-31 |
| Hub design | Fork assembly |
| Type of bearing | Without bearing |
| Shaft diameter [mm]. | 35 |
| Mounting length [mm] | 71 |
| Hub length [mm] | 71 |
| Rim colour | Red |
| Load capacity complete wheel [kg] | 200 |
| Speed complete wheel [km/h] | 5 |



Technical Informations

| Assembly Item no. Tyres • | 19800501 |
|---------------------------|---------------|
| Brand | Starco |
| Tread pattern | ST-31 |
| Carcass properties | Polyurethane |
| Antistatic | No |
| Shore | 60 |
| Tyre colour | Yellow |
| ECE regulation number | not necessary |
| Section width (mm) | 80 |
| Assembly Item no. Rim • | 39600080 |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



| Valid rim size | 2.10 A x 4 |
|-----------------------------|----------------|
| Load capacity of rim 1 [kg] | 280 |
| Speed Rims 1 [km/h] | 20 |
| Maximum speed [km/h]. | 5 |
| Type of drive | Towed axle |
| Hump | kein Hump |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL3002 |
| Verschweißung beidseitig | No |
| Offset hub | No |
| Additional socket required | No |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 11.3 |