

WHEELS

| | |
|-----------------------------------|------------|
| Product group | Wheels |
| Item number | 59696120 |
| Valid wheel size | 6.00 - 9 |
| Brand | Deli |
| Tread pattern | S-369 |
| Valid rim size | 4.00 E x 9 |
| Rim connection | 5/94/140 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 1300 |
| Speed complete wheel [km/h] | 10 |



Technical Informations

| | |
|-----------------------------|---------------|
| Assembly Item no. Tyres | • 19110160 |
| LI / SI / PR | 118 A2, 6 PR |
| Load capacity 1 [kg] | 1320 |
| Speed 1 [km/h]. | 10 |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 11,04 |
| ECE regulation number | not necessary |
| Section width (mm) | 170 |
| Stat. radius (SLR) [mm] | 230 |
| Rolling circumference [mm]. | 1474 |

| | |
|---------------------------------|----------------|
| E-Ready | No |
| Assembly Item no. Rim | • 39600350 |
| Load capacity of rim 1 [kg] | 1300 |
| Speed Rims 1 [km/h] | 10 |
| Maximum speed [km/h]. | 10 |
| Maximum air pressure [bar]. | 5,00 |
| Type of drive | Towed axle |
| Hump | kein Hump |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 5 |
| Bolt hole diameter [mm] | 18.5 |
| Countersinking | Cone |
| Countersinking of the cone [°]. | C60 |
| hub hole diameter [mm]. | 94 |
| Bolt hole circle diameter [mm] | 140 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 16.0 |
| Preassembled valve | No |
| Valve design | Rubber valve |
| Valve length [mm] | 38 |
| Valve angle [°] | gerade |

| | |
|--------------------|---------|
| Colour of cap | Black |
| Valve cap Material | Plastic |
