

## WHEELS

|                                   |                  |
|-----------------------------------|------------------|
| Product group                     | Wheels           |
| Item number                       | 59696159         |
| Valid wheel size                  | 195 / 70 R 14    |
| Brand                             | GT Radial        |
| Tread pattern                     | KargoMax ST 4000 |
| Valid rim size                    | 5.5 J x 14 H2    |
| Rim connection                    | 5/67/112         |
| Bolt hole design                  | E12              |
| Offset (mm)                       | +30              |
| Rim colour                        | Silver           |
| Load capacity complete wheel [kg] | 710              |
| Speed complete wheel [km/h]       | 140              |



## Technical Informations

|                            |                |
|----------------------------|----------------|
| Assembly Item no. Tyres    | • 19866021     |
| LI / SI / PR               | 96 N           |
| Load capacity 1 [kg]       | 710            |
| Speed 1 [km/h].            | 140            |
| M+S                        | M+S            |
| Antistatic                 | No             |
| Tyre colour                | Black          |
| Nettogewicht [kg] (gültig) | 18,54          |
| ECE regulation number      | ECE 30 ECE 117 |
| Section width (mm)         | 201            |
| Stat. radius (SLR) [mm]    | 285            |

|                             |            |
|-----------------------------|------------|
| Rolling circumference [mm]. | 1922       |
| Rolling resistance          | C          |
| Wet grip                    | C          |
| Rolling noise [db].         | 72         |
| Rolling noise level         | B          |
| E-Ready                     | No         |
| Assembly Item no. Rim       | • 39600672 |
| Load capacity of rim 1 [kg] | 950        |
| Speed Rims 1 [km/h]         | 140        |
| Maximum speed [km/h].       | 140        |
| Maximum air pressure [bar]. | 3,10       |
| Type of drive               | Towed axle |
| Hump                        | H2         |
| Single / multi-part         | einteilig  |
| Rim material                | steel      |
| RAL                         | RAL9006    |
| Colour type                 | Glossy     |
| Cavity Sealed               | No         |
| Disc thickness [mm]         | 5          |
| Ventilation holes           | No         |
| Verschweißung beidseitig    | No         |
| Rim centering               | BC         |
| Number of bolt holes        | 5          |
| Bolt hole diameter [mm]     | 16         |
| Countersinking              | Sphere     |
| Spherical countersink [mm]. | R12        |
| hub hole diameter [mm].     | 67         |

---

|                                       |                |
|---------------------------------------|----------------|
| <b>Bolt hole circle diameter [mm]</b> | 112            |
| <b>Valve seat</b>                     | External Valve |
| <b>Valve hole diameter [mm]</b>       | 11.3           |
| <b>Preassembled valve</b>             | No             |
| <b>Valve design</b>                   | Rubber valve   |
| <b>Valve designation ETRTO</b>        | V2.03.1        |
| <b>Valve length [mm]</b>              | 43.0           |
| <b>Valve angle [°]</b>                | gerade         |