

## WHEELS

Product group	Wheels
Item number	59696208
Valid wheel size	4.80 / 4.00 - 8
Brand	Kenda
Tread pattern	K352
LI / SI / PR	6 PR
TL/TT	TL
Hub design	Fork assembly
Type of bearing	Without bearing
Shaft diameter [mm].	35
Mounting length [mm]	71
Hub length [mm]	71
Rim colour	Red
Load capacity complete wheel [kg]	340
Speed complete wheel [km/h]	16



## Technical Informations

Assembly Item no. Tyres	• 19211170
LI / SI / PR	6 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K352
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary

Maximum air pressure [bar].	6,89
Section width (mm)	103
Rolling circumference [mm].	1233
Assembly Item no. Rim	• 39600034
Valid rim size	2.50 A x 8
Load capacity of rim 1 [kg]	350
Speed Rims 1 [km/h]	16
Maximum speed [km/h].	16
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	plastic
RAL	RAL3000
Verschweißung beidseitig	No
Offset hub	No
Additional socket required	No
Valve seat	External Valve
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0