

## **WHEELS**

Product group	Wheels
Item number	59696262
Valid wheel size	4.80 / 4.00 - 8
Brand	Deli
Tread pattern	S-369
LI/SI/PR	67 A4, 4 PR
титт	TL
Hub design	Fork assembly
Type of bearing	Without bearing
Shaft diameter [mm].	35
Mounting length [mm]	71
Hub length [mm]	71
Rim colour	Red
Load capacity complete wheel [kg]	305
Speed complete wheel [km/h]	16



## **Technical Informations**

Assembly Item no. Tyres	19110109
LI / SI / PR	67 A4, 4 PR
TL/TT	TL
Brand	Deli
Tread pattern	S-369
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Maximum air pressure [bar].	3,50
Section width (mm)	104
Stat. radius (SLR) [mm]	177
Rolling circumference [mm].	1205
Tread depth (mm)	2,2
Assembly Item no. Rim •	39600034
Valid rim size	2.50 A x 8
Load capacity of rim 1 [kg]	350
Speed Rims 1 [km/h]	16
Maximum speed [km/h].	20
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	plastic
RAL	RAL3000
Verschweißung beidseitig	No
Offset hub	No
Additional socket required	No
Valve seat	External Valve
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0