

WHEELS

Product group	Wheels
Item number	59696277
Valid wheel size	18 x 8.50 - 8
Brand	Deli
Tread pattern	S-317
LI/SI/PR	74 A6, 4 PR
TUTT	TT
Hub design	Fork assembly
Type of bearing	Ball bearing
Shaft diameter [mm].	25
Mounting length [mm]	90
Hub length [mm]	90
Rim colour	Silver
Load capacity complete wheel [kg]	375
Speed complete wheel [km/h]	30



Technical Informations

Assembly Item no. Tyres	19110142
LI / SI / PR	74 A6, 4 PR
TL/TT	тт
Brand	Deli
Tread pattern	S-317
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Maximum air pressure [bar]. 1,50 Section width (mm) 216 Stat. radius (SLR) [mm] 186 Rolling circumference [mm]. 1302 Tread depth (mm) 4,5 Assembly Item no. Rim • 30895260 Valid rim size 7.00 x 8 Load capacity of rim 1 [kg] 425 Speed Rims 1 [km/h] 40 Maximum speed [km/h]. 30 Type of drive Towed axle Hump kein Hump Single / multi-part einteilig Rim material steel RAL RAL9006 Verschweißung beidseitig No Offset hub No Additional socket required No Valve seat External Valve Valve hole diameter [mm] 11.3		
Stat. radius (SLR) [mm] 186	Maximum air pressure [bar].	1,50
Tread depth (mm) 4,5 Assembly Item no. Rim • 30895260 Valid rim size 7.00 x 8 Load capacity of rim 1 [kg] 425 Speed Rims 1 [km/h] 40 Maximum speed [km/h]. 30 Type of drive Towed axle Hump kein Hump Single / multi-part einteilig Rim material steel RAL RAL9006 Verschweißung beidseitig No Offset hub No Additional socket required No Valve seat External Valve	Section width (mm)	216
Tread depth (mm) 4,5 Assembly Item no. Rim • 30895260 Valid rim size 7.00 x 8 Load capacity of rim 1 [kg] 425 Speed Rims 1 [km/h] 40 Maximum speed [km/h]. 30 Type of drive Towed axle Hump kein Hump Single / multi-part einteilig Rim material steel RAL RAL9006 Verschweißung beidseitig No Offset hub No Additional socket required No Valve seat External Valve	Stat. radius (SLR) [mm]	186
Assembly Item no. Rim • 30895260 Valid rim size 7.00 l x 8 Load capacity of rim 1 [kg] 425 Speed Rims 1 [km/h] 40 Maximum speed [km/h]. 30 Type of drive Towed axle Hump kein Hump Single / multi-part einteilig Rim material steel RAL RAL9006 Verschweißung beidseitig No Offset hub No Additional socket required No Valve seat External Valve	Rolling circumference [mm].	1302
Valid rim size 7.00 l x 8 Load capacity of rim 1 [kg] 425 Speed Rims 1 [km/h] 40 Maximum speed [km/h]. 30 Type of drive Towed axle Hump kein Hump Single / multi-part einteilig Rim material steel RAL RAL9006 Verschweißung beidseitig No Offset hub No Additional socket required No Valve seat External Valve	Tread depth (mm)	4,5
Load capacity of rim 1 [kg] 425 Speed Rims 1 [km/h] 40 Maximum speed [km/h]. 30 Type of drive Towed axle Hump kein Hump Single / multi-part einteilig Rim material steel RAL RAL9006 Verschweißung beidseitig No Offset hub No Additional socket required No Valve seat External Valve	Assembly Item no. Rim •	30895260
Speed Rims 1 [km/h] 40 Maximum speed [km/h]. 30 Type of drive Towed axle Hump kein Hump Single / multi-part einteilig Rim material steel RAL RAL9006 Verschweißung beidseitig No Offset hub No Additional socket required No Valve seat External Valve	Valid rim size	7.00 I x 8
Maximum speed [km/h]. 30 Type of drive Towed axle Hump kein Hump Single / multi-part einteilig Rim material steel RAL RAL9006 Verschweißung beidseitig No Offset hub No Additional socket required No Valve seat External Valve	Load capacity of rim 1 [kg]	425
Type of drive Towed axle Hump kein Hump Single / multi-part einteilig Rim material steel RAL RAL9006 Verschweißung beidseitig No Offset hub No Additional socket required No Valve seat External Valve	Speed Rims 1 [km/h]	40
Hump kein Hump Single / multi-part einteilig Rim material steel RAL RAL9006 Verschweißung beidseitig No Offset hub No Additional socket required No Valve seat External Valve	Maximum speed [km/h].	30
Single / multi-part einteilig Rim material steel RAL RAL9006 Verschweißung beidseitig No Offset hub No Additional socket required No Valve seat External Valve	Type of drive	Towed axle
Rim material steel RAL RAL9006 Verschweißung beidseitig No Offset hub No Additional socket required No Valve seat External Valve	Hump	kein Hump
RAL RAL9006 Verschweißung beidseitig No Offset hub No Additional socket required No Valve seat External Valve	Single / multi-part	einteilig
Verschweißung beidseitig No Offset hub No Additional socket required No Valve seat External Valve	Rim material	steel
Offset hub No Additional socket required No Valve seat External Valve	RAL	RAL9006
Additional socket required No Valve seat External Valve	Verschweißung beidseitig	No
Valve seat External Valve	Offset hub	No
	Additional socket required	No
Valve hole diameter [mm] 11.3	Valve seat	External Valve
	Valve hole diameter [mm]	11.3
Valve designation TR 13	Valve designation	TR 13