

## WHEELS

Product group	Wheels
Item number	59696301
Valid wheel size	20.5 x 10.0 - 10
Brand	Kenda
Tread pattern	K399 Loadstar
Valid rim size	8.50 I x 10 H2
Rim connection	5/67/112
Bolt hole design	E12
Offset (mm)	-4
Rim colour	Silver
Load capacity complete wheel [kg]	750
Speed complete wheel [km/h]	130



## Technical Informations

Assembly Item no. Tyres	• 19266070
LI / SI / PR	98 M, 8 PR
Load capacity 1 [kg]	750
Speed 1 [km/h].	130
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	16,27
ECE regulation number	ECE 54
Section width (mm)	253
Stat. radius (SLR) [mm]	230
Rolling circumference [mm].	1563

E-Ready	No
Assembly Item no. Rim	• 39600281
Load capacity of rim 1 [kg]	750
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	130
Maximum air pressure [bar].	6,00
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade