

## WHEELS

|                                   |               |
|-----------------------------------|---------------|
| Product group                     | Wheels        |
| Item number                       | 59696343      |
| Valid wheel size                  | 16 x 6.50 - 8 |
| Brand                             | Kenda         |
| Tread pattern                     | K357          |
| Valid rim size                    | 5.50 A x 8    |
| Rim connection                    | 4/60/100      |
| Bolt hole design                  | D12           |
| Rim colour                        | Silver        |
| Load capacity complete wheel [kg] | 200           |
| Speed complete wheel [km/h]       | 100           |



## Technical Informations

|                            |                     |
|----------------------------|---------------------|
| Assembly Item no. Tyres    | • 19211177          |
| LI / SI / PR               | 52 A4 / 63 A4, 4 PR |
| Load capacity 1 [kg]       | 200                 |
| Speed 1 [km/h].            | 20                  |
| Load capacity 2 [kg]       | 272                 |
| Speed 2 [km/h].            | 20                  |
| Antistatic                 | No                  |
| Tyre colour                | Black               |
| Nettogewicht [kg] (gültig) | 6,10                |
| ECE regulation number      | ECE 106             |
| Section width (mm)         | 163                 |

|                                |                |
|--------------------------------|----------------|
| Rolling circumference [mm].    | 1268.00        |
| E-Ready                        | No             |
| Assembly Item no. Rim          | • 30655030     |
| Load capacity of rim 1 [kg]    | 575            |
| Speed Rims 1 [km/h]            | 25             |
| Load capacity of rim 2 [kg]    | 350            |
| Speed Rims 2 [km/h]            | 100            |
| Maximum speed [km/h].          | 100            |
| Maximum air pressure [bar].    | 1,90           |
| Type of drive                  | Towed axle     |
| Hump                           | kein Hump      |
| Single / multi-part            | einteilig      |
| Rim material                   | steel          |
| RAL                            | RAL9006        |
| Cavity Sealed                  | No             |
| Ventilation holes              | No             |
| Verschweißung beidseitig       | No             |
| Rim centering                  | BC             |
| Number of bolt holes           | 4              |
| Bolt hole diameter [mm]        | 16             |
| Countersinking                 | Sphere         |
| Spherical countersink [mm].    | R12            |
| hub hole diameter [mm].        | 60             |
| Bolt hole circle diameter [mm] | 100            |
| Valve seat                     | External Valve |
| Valve hole diameter [mm]       | 11.3           |
| Preassembled valve             | No             |

---

|                         |              |
|-------------------------|--------------|
| Valve design            | Rubber valve |
| Valve designation ETRTO | V2.03.1      |
| Valve length [mm]       | 43.0         |
| Valve angle [°]         | gerade       |