

## **WHEELS**

Product group	Wheels
Item number	59696367
Valid wheel size	18 x 8.50 - 8
Brand	Kenda
Tread pattern	K401H
LI / SI / PR	81 A4 / 69 A4, 6 PR
TL/TT	TL
Hub design	Fork assembly
Type of bearing	Ball bearing
Shaft diameter [mm].	25
Mounting length [mm]	90
Hub length [mm]	90
Rim colour	Silver
Load capacity complete wheel [kg]	325
Speed complete wheel [km/h]	20



## **Technical Informations**

Assembly Item no. Tyres	19211203
LI / SI / PR	81 A4 / 69 A4, 6 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K401H
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Maximum air pressure [bar]. 2,30  Section width (mm) 218  Rolling circumference [mm]. 1358.00  Assembly Item no. Rim • 30895260  Valid rim size 7.001 x 8  Load capacity of rim 1 [kg] 425  Speed Rims 1 [km/h] 40  Maximum speed [km/h]. 20  Type of drive Towed axle  Hump kein Hump  Single / multi-part einteilig  Rim material steel	
Rolling circumference [mm]. 1358.00  Assembly Item no. Rim • 30895260  Valid rim size 7.00 l x 8  Load capacity of rim 1 [kg] 425  Speed Rims 1 [km/h] 40  Maximum speed [km/h]. 20  Type of drive Towed axle  Hump kein Hump  Single / multi-part einteilig	
Assembly Item no. Rim • 30895260  Valid rim size 7.001 x 8  Load capacity of rim 1 [kg] 425  Speed Rims 1 [km/h] 40  Maximum speed [km/h]. 20  Type of drive Towed axle  Hump kein Hump  Single / multi-part einteilig	
Valid rim size 7.00 l x 8  Load capacity of rim 1 [kg] 425  Speed Rims 1 [km/h] 40  Maximum speed [km/h]. 20  Type of drive Towed axle  Hump kein Hump  Single / multi-part einteilig	
Load capacity of rim 1 [kg] 425  Speed Rims 1 [km/h] 40  Maximum speed [km/h]. 20  Type of drive Towed axle  Hump kein Hump  Single / multi-part einteilig	
Speed Rims 1 [km/h] 40  Maximum speed [km/h]. 20  Type of drive Towed axle  Hump kein Hump  Single / multi-part einteilig	
Maximum speed [km/h]. 20  Type of drive Towed axle  Hump kein Hump  Single / multi-part einteilig	
Type of drive Towed axle  Hump kein Hump Single / multi-part einteilig	
Hump kein Hump  Single / multi-part einteilig	
Single / multi-part einteilig	
Rim material steel	
RAL RAL9006	
Verschweißung beidseitig No	
Offset hub No	
Additional socket required No	
Valve seat External Valve	
Valve hole diameter [mm] 11.3	
Valve design Rubber valve	
Valve length [mm] 38	
Valve cap Material Plastic	
Colour of cap Black	