

WHEELS

Product group	Wheels
Item number	59696375
Valid wheel size	33 x 12.50 - 16.5
Brand	Kenda
Tread pattern	K500 Super Turf
Valid rim size	9.75 x 16.5 H2
Rim connection	5/108/139.5
Offset (mm)	-25
Rim colour	Silver
Load capacity complete wheel [kg]	1030
Speed complete wheel [km/h]	20



Technical Informations

Assembly Item no. Tyres	• 19211360
LI / SI / PR	97 A4 / 109 A4, 4 PR
Load capacity 1 [kg]	730
Speed 1 [km/h].	20
Load capacity 2 [kg]	1030
Speed 2 [km/h].	20
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	36,84
ECE regulation number	ECE 106
Section width (mm)	318

Stat. radius (SLR) [mm]	383
Rolling circumference [mm].	2501
E-Ready	No
Assembly Item no. Rim	• 39600996
Load capacity of rim 1 [kg]	1610
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	1030
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	20
Maximum air pressure [bar].	2,10
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	HB
Number of bolt holes	5
Bolt hole diameter [mm]	17.5
hub hole diameter [mm].	108
Bolt hole circle diameter [mm]	139.5
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve

Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade