

WHEELS

Product group	Wheels
Item number	59696535
Valid wheel size	5.00 - 8
Brand	Kenda
Tread pattern	K385
Valid rim size	3.00 D x 8
Rim connection	4/60/100
Bolt hole design	D12
Rim colour	Silver
Load capacity complete wheel [kg]	300
Speed complete wheel [km/h]	100



Technical Informations

Assembly Item no. Tyres •	19266055
LI / SI / PR	77 M, 6 PR
Load capacity 1 [kg]	412
Speed 1 [km/h].	130
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	6,35
ECE regulation number	ECE 54
Section width (mm)	140
E-Ready	No
Assembly Item no. Rim •	30655020

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity of rim 1 [kg]	300
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	5,20
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	60
Bolt hole circle diameter [mm]	100
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No