

WHEELS

| | |
|-----------------------------------|-----------------|
| Product group | Wheels |
| Item number | 59696586 |
| Valid wheel size | 4.80 / 4.00 - 8 |
| Brand | Kenda |
| Tread pattern | K385 |
| LI / SI / PR | 71 M, 8 PR |
| TL/TT | TL |
| Hub design | Fork assembly |
| Type of bearing | Ball bearing |
| Shaft diameter [mm]. | 25 |
| Mounting length [mm] | 100 |
| Hub length [mm] | 100 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 305 |
| Speed complete wheel [km/h] | 16 |



Technical Informations

| | |
|-------------------------|------------|
| Assembly Item no. Tyres | • 19800365 |
| LI / SI / PR | 71 M, 8 PR |
| TL/TT | TL |
| Brand | Kenda |
| Tread pattern | K385 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54 |

| | |
|-----------------------------|----------------|
| Maximum air pressure [bar]. | 6,30 |
| Section width (mm) | 122 |
| Assembly Item no. Rim | • 39600060 |
| Valid rim size | 2.50 A x 8 |
| Load capacity of rim 1 [kg] | 305 |
| Speed Rims 1 [km/h] | 16 |
| Maximum speed [km/h]. | 16 |
| Type of drive | Towed axle |
| Hump | kein Hump |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Verschweißung beidseitig | No |
| Offset hub | No |
| Additional socket required | No |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 11.3 |
| Valve design | Rubber valve |
| Valve designation ETRTO | V2.03.6 |
| Valve length [mm] | 33.0 |