

## WHEELS

Product group	Wheels
Item number	59719828
Valid wheel size	155 / 70 R 12 C
Brand	Security
Tread pattern	TR603
Valid rim size	4.5 J x 12 H2
Rim connection	5/114.5/165.1
Bolt hole design	E18
Rim colour	Silver
Load capacity complete wheel [kg]	900
Speed complete wheel [km/h]	140



## Technical Informations

Assembly Item no. Tyres	• 18366121
LI / SI / PR	104 / 102 N
Load capacity 1 [kg]	900
Speed 1 [km/h].	140
Load capacity 3 [kg]	850
Speed 3 [km/h].	140
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	15,13
ECE regulation number	ECE 54 ECE 117

Section width (mm)	157
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 39600335
Load capacity of rim 1 [kg]	900
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	6,30
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	18.5
Countersinking	Cone
Countersinking of the cone [°].	C80
hub hole diameter [mm].	114.5
Bolt hole circle diameter [mm]	165.1
Valve seat	External Valve

---

Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade