

WHEELS

Product group	Wheels
Item number	59737465
Valid wheel size	195 / 50 R 13 C
Brand	Trailermaxx
Tread pattern	CR-966
Valid rim size	6 J x 13 H2
Rim connection	5/66.6/112
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	900
Speed complete wheel [km/h]	140



Technical Informations

Assembly Item no. Tyres	• 10745200
LI / SI / PR	104 / 101 N
Load capacity 1 [kg]	900
Speed 1 [km/h].	140
Load capacity 3 [kg]	825
Speed 3 [km/h].	140
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	13,43
ECE regulation number	ECE 54 ECE 117

Section width (mm)	188
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 39800305
Load capacity of rim 1 [kg]	900
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	140
Maximum air pressure [bar].	6,25
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Single / multi-part	einteilig
Rim material	aluminium
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	10
Countersinking	Cone
Countersinking of the cone [°].	C60
hub hole diameter [mm].	66.6
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Preassembled valve	No

Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade