

WHEELS

Product group	Wheels
Item number	59737470
Valid wheel size	195 / 50 R 13 C
Brand	Security
Tread pattern	TR603
Valid rim size	5.5 J x 13 H2
Rim connection	5/66.5/112
Bolt hole design	E12
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	900
Speed complete wheel [km/h]	140



Bohnenkamp
■ ■ ● Moving Professionals

Technical Informations

Assembly Item no. Tyres	• 18345331
LI / SI / PR	104 / 101 N
Load capacity 1 [kg]	900
Speed 1 [km/h].	140
Load capacity 3 [kg]	825
Speed 3 [km/h].	140
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	15,90
ECE regulation number	ECE 54 ECE 117

Section width (mm)	201
Tread depth (mm)	6,5
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 30055081
Load capacity of rim 1 [kg]	900
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	6,50
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	66.5
Bolt hole circle diameter [mm]	112

Valve seat	External Valve
Valve hole diameter [mm]	12.5
Preassembled valve	No
Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade