

WHEELS

Product group	Wheels
Item number	59737477
Valid wheel size	195 / 50 R 13 C
Brand	Kenda
Tread pattern	KR500 Winter Trailer
Valid rim size	6 J x 13 H2
Rim connection	5/67/112
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	900
Speed complete wheel [km/h]	140



Bohnenkamp
Moving Professionals

Technical Informations

Assembly Item no. Tyres	• 19266110
LI / SI / PR	104 / 101 N
Load capacity 1 [kg]	900
Speed 1 [km/h].	140
Load capacity 3 [kg]	825
Speed 3 [km/h].	140
M+S	M+S
3PMSF	3PMSF
Carcass properties	Spike-ability
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	14,73
ECE regulation number	ECE 54 ECE 117
Section width (mm)	192
Rolling resistance	E
Wet grip	B
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 39800420
Load capacity of rim 1 [kg]	900
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	6,55
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	aluminium
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112

Valve seat	External Valve
Valve hole diameter [mm]	11.4
Preassembled valve	No
Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade