

WHEELS

Product group	Wheels
Item number	59737479
Valid wheel size	12 - 16.5
Brand	Kenda
Tread pattern	K395 Power Grip
Valid rim size	9.75 x 16.5 H2
Rim connection	5/108/139.5
Offset (mm)	-25
Rim colour	Silver
Load capacity complete wheel [kg]	1610
Speed complete wheel [km/h]	10
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 19271114
LI / SI / PR	145 A2, 12 PR
Load capacity 1 [kg]	2900
Speed 1 [km/h].	10
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	47,43
ECE regulation number	ECE 106
Section width (mm)	316
Stat. radius (SLR) [mm]	401

Rolling circumference [mm].	2610
Tread depth (mm)	19,0
E-Ready	No
Assembly Item no. Rim	• 39600996
Load capacity of rim 1 [kg]	1610
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	1030
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	10
Maximum air pressure [bar].	5,50
Number of bolt holes	5
hub hole diameter [mm].	108
Bolt hole circle diameter [mm]	139.5
Bolt hole diameter [mm]	17.5
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Single / multi-part	einteilig
Rim centering	HB
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
TPMS-kompatibles Ventil	No

Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade