

WHEELS

Product group	Wheels
Item number	59737481
Valid wheel size	23 x 8.50 - 12
Brand	Kenda
Tread pattern	K395 Power Grip
Valid rim size	7.00 I x 12 H2
Rim connection	5/80/114.3
Offset (mm)	-10.5
Rim colour	Silver
Load capacity complete wheel [kg]	825
Speed complete wheel [km/h]	10
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 19271084
LI / SI / PR	101 A2, 6 PR
Load capacity 1 [kg]	825
Speed 1 [km/h].	10
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	17,87
ECE regulation number	ECE 106
Section width (mm)	216
Stat. radius (SLR) [mm]	266

Rolling circumference [mm].	1736
Tread depth (mm)	12,0
E-Ready	No
Assembly Item no. Rim	• 39600418
Load capacity of rim 1 [kg]	900
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	10
Maximum air pressure [bar].	3,10
Number of bolt holes	5
hub hole diameter [mm].	80
Bolt hole circle diameter [mm]	114.3
Bolt hole diameter [mm]	13
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1

Valve length [mm]	43.0
Valve angle [°]	gerade
