

WHEELS

Product group	Wheels
Item number	59738007
Valid wheel size	255 / 65 R 16
Brand	Yokohama
Tread pattern	Geolandar A/T G015
Valid rim size	W 8 x 16
Rim connection	5/94/140
Bolt hole design	A1
Offset (mm)	+10
Rim colour	Silver
Load capacity complete wheel [kg]	1700
Speed complete wheel [km/h]	50
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 19821351
LI / SI / PR	109 H
Load capacity 1 [kg]	1030
Speed 1 [km/h].	210
M+S	M+S
3PMSF	3PMSF
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	31,81

ECE regulation number	ECE 30 ECE 117
Section width (mm)	262
Stat. radius (SLR) [mm]	333
Rolling circumference [mm].	2254
Tread depth (mm)	9,7
Rolling resistance	E
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 33060102
Load capacity of rim 1 [kg]	1900
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2250
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	50
Maximum air pressure [bar].	3,50
Number of bolt holes	5
Bolt hole design EUWA	B14 ES 28
hub hole diameter [mm].	94
Bolt hole circle diameter [mm]	140
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig

Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade