

WHEELS

Product group	Wheels
Item number	59772860
Valid wheel size	175 / 65 R 15
Brand	Trailermaxx
Tread pattern	CR-966
Valid rim size	5.5 J x 15 H2
Rim connection	5/66/112
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	650
Speed complete wheel [km/h]	140



Technical Informations

Assembly Item no. Tyres	• 10745510
LI / SI / PR	93 N (95 J)
Load capacity 1 [kg]	650
Speed 1 [km/h].	140
Load capacity 2 [kg]	690
Speed 2 [km/h].	100
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	18,42
ECE regulation number	ECE 54 ECE 117
Section width (mm)	177

Stat. radius (SLR) [mm]	274
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 39600303
Load capacity of rim 1 [kg]	900
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	6,25
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	Yes
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	17
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	66
Bolt hole circle diameter [mm]	112
Valve seat	External Valve

Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade