

WHEELS

Product group	Wheels
Item number	59773181
Valid wheel size	28 x 12.5 - 15
Brand	BKT
Tread pattern	Power Trax HD Forklift
Valid rim size	9.75 - 15
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	3250
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15771174
LI / SI / PR	149 A8, 24 PR
Load capacity 1 [kg]	3250
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	61,96
ECE regulation number	ECE 106
Section width (mm)	304
Tread depth (mm)	19,0
E-Ready	No

Assembly Item no. Rim	• 31610066
Load capacity of rim 1 [kg]	3250
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	10,00
Number of bolt holes	8
Bolt hole design EUWA	B18 ES 32
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Countersinking	Sphere
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	mehrteilig
Quantity multi-piece	four-part
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	12.0
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15x123
Preassembled valve	No
TPMS-kompatibles Ventil	No