

## WHEELS

Product group	Wheels
Item number	59900702
Valid wheel size	320 / 55 - 15
Brand	Carlstar
Tread pattern	Multi Trac C/S
Valid rim size	10 x 15
Rim connection	5/94/140
Bolt hole design	A1
Rim colour	Silver
Load capacity complete wheel [kg]	1120
Speed complete wheel [km/h]	50



## Technical Informations

Assembly Item no. Tyres	• 12500689
LI / SI / PR	112 B, 10 PR
Load capacity 1 [kg]	1120
Speed 1 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	35,53
ECE regulation number	ECE 106
Section width (mm)	318
Stat. radius (SLR) [mm]	344
Rolling circumference [mm].	2291

Tread depth (mm)	8,9
E-Ready	No
Assembly Item no. Rim	• 33060023
Load capacity of rim 1 [kg]	2950
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2500
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	50
Maximum air pressure [bar].	4,15
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole design EUWA	B14 ES 28
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	94
Bolt hole circle diameter [mm]	140
Valve seat	External Valve

---

Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade