

WHEELS

Product group	Wheels
Item number	59900708
Valid wheel size	31 x 13.50 - 15
Brand	Carlstar
Tread pattern	Multi Trac C/S
Valid rim size	10 LB x 15 H2
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	-35
Rim colour	Silver
Load capacity complete wheel [kg]	1550
Speed complete wheel [km/h]	20



Technical Informations

Assembly Item no. Tyres	• 12500701
LI / SI / PR	123 A4 / 114 B, 8 PR
Load capacity 1 [kg]	1550
Speed 1 [km/h].	20
Load capacity 2 [kg]	1180
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	40,75
ECE regulation number	ECE 106
Section width (mm)	340

Stat. radius (SLR) [mm]	356
Rolling circumference [mm].	2373
Tread depth (mm)	11,1
E-Ready	No
Assembly Item no. Rim	• 30810100
Load capacity of rim 1 [kg]	1800
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,10
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Preassembled valve	No

Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade