

## WHEELS

Product group	Wheels
Item number	59909174
Valid wheel size	280 / 70 R 18
Brand	BKT
Tread pattern	Agrimax RT 765
Valid rim size	W 9 x 18 H2
Rim connection	5/108/139.5
Offset (mm)	-13
Rim colour	Silver
Load capacity complete wheel [kg]	1180
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15726566
LI / SI / PR	114 A8 / 114 B
Load capacity 1 [kg]	1180
Speed 1 [km/h].	40
Load capacity 2 [kg]	1180
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	52,91
ECE regulation number	ECE 106

Section width (mm)	282
Stat. radius (SLR) [mm]	381
Rolling circumference [mm].	2547
Tread depth (mm)	32,0
Number of lugs	17x2
Tyre capacity 75% [ltr.]	49.5
E-Ready	No
Assembly Item no. Rim	• 39600419
Load capacity of rim 1 [kg]	750
Speed Rims 1 [km/h]	30
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,40
Number of bolt holes	5
hub hole diameter [mm].	108
Bolt hole circle diameter [mm]	139.5
Bolt hole diameter [mm]	17.5
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7

---

Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade