

WHEELS

| Product group | Wheels |
|-----------------------------------|--------------------|
| Item number | 59909210 |
| Valid wheel size | 33 x 12 - 20 / 7.5 |
| Brand | Galaxy |
| Tread pattern | Beefy Baby SDS |
| Valid rim size | 7.5 - 20 |
| Rim connection | 8/221/275 |
| Bolt hole design | A3 |
| Offset (mm) | +35 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 4000 |
| Speed complete wheel [km/h] | 25 |





Technical Informations

| Assembly Item no. Tyres • | 12025255 |
|-----------------------------|------------------|
| Carcass properties | LIP Solid Rubber |
| Direction | Right |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 139,00 |
| ECE regulation number | not necessary |
| Section width (mm) | 285 |
| E-Ready | No |
| Assembly Item no. Rim • | 33060152 |
| Load capacity of rim 1 [kg] | 6500 |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



| Speed Rims 1 [km/h] | 25 |
|--------------------------------|-------------------------------|
| Maximum speed [km/h]. | 25 |
| Type of drive | Angetriebene & gezogene Achse |
| Hump | kein Hump |
| Single / multi-part | mehrteilig |
| Quantity multi-piece | two-part |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Rim design industry | Lip |
| Disc thickness [mm] | 10 |
| Knurling | without knurling |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 8 |
| Bolt hole design EUWA | B22 ES 36 |
| Bolt hole diameter [mm] | 27 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R18 |
| hub hole diameter [mm]. | 221 |
| Bolt hole circle diameter [mm] | 275 |
| Valve seat | External Valve |
| Preassembled valve | No |