

WHEELS

Product group	Wheels
Item number	59910024
Valid wheel size	23 x 10.50 - 12
Brand	BKT
Tread pattern	TR 315
Valid rim size	8.50 JA x 12 H2
Rim connection	6/161/205
Rim colour	Silver
Load capacity complete wheel [kg]	950
Speed complete wheel [km/h]	15



Technical Informations

Assembly Item no. Tyres	• 15710494
LI / SI / PR	106 A3 /102 A6, 8 PR
Load capacity 1 [kg]	950
Speed 1 [km/h].	15
Load capacity 2 [kg]	850
Speed 2 [km/h].	30
Direction	Left
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	17,97
ECE regulation number	ECE 106

Section width (mm)	255
Stat. radius (SLR) [mm]	260
Rolling circumference [mm].	1682
Tread depth (mm)	15,5
E-Ready	No
Assembly Item no. Rim	• 30855026
Load capacity of rim 1 [kg]	1150
Speed Rims 1 [km/h]	5
Load capacity of rim 2 [kg]	950
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	30
Maximum air pressure [bar].	3,00
Type of drive	Towed axle
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Number of drain holes	3
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Cone
Countersinking of the cone [°].	C90

hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade