

WHEELS

| | |
|-----------------------------------|-----------------|
| Product group | Wheels |
| Item number | 59910026 |
| Valid wheel size | 23 x 10.50 - 12 |
| Brand | BKT |
| Tread pattern | TR 315 |
| Valid rim size | 7.00 I X 12 |
| Rim connection | 5/94/140 |
| Bolt hole design | A1 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 850 |
| Speed complete wheel [km/h] | 30 |



Technical Informations

| | |
|----------------------------|----------------------|
| Assembly Item no. Tyres | • 15710494 |
| LI / SI / PR | 106 A3 /102 A6, 8 PR |
| Load capacity 1 [kg] | 950 |
| Speed 1 [km/h]. | 15 |
| Load capacity 2 [kg] | 850 |
| Speed 2 [km/h]. | 30 |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 18,14 |
| ECE regulation number | ECE 106 |
| Section width (mm) | 255 |

| | |
|--------------------------------|----------------|
| Stat. radius (SLR) [mm] | 260 |
| Rolling circumference [mm]. | 1682 |
| Tread depth (mm) | 15,5 |
| E-Ready | No |
| Assembly Item no. Rim | • 30820110 |
| Load capacity of rim 1 [kg] | 1500 |
| Speed Rims 1 [km/h] | 40 |
| Maximum speed [km/h]. | 30 |
| Maximum air pressure [bar]. | 3,00 |
| Type of drive | Towed axle |
| Hump | kein Hump |
| Valve protection | VS H |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Number of drain holes | 1 |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 5 |
| Bolt hole design EUWA | B14 ES 28 |
| Bolt hole diameter [mm] | 18.5 |
| Spherical countersink [mm]. | R14 |
| hub hole diameter [mm]. | 94 |
| Bolt hole circle diameter [mm] | 140 |
| Valve seat | External Valve |

| | |
|--------------------------|--------------|
| Valve hole diameter [mm] | 11.3 |
| Preassembled valve | No |
| Valve design | Rubber valve |
| Valve designation ETRTO | V2.03.3 |
| Valve length [mm] | 43.0 |
| Valve angle [°] | gerade |