

WHEELS

Product group	Wheels
Item number	59910030
Valid wheel size	23 x 8.50 - 12
Brand	BKT
Tread pattern	LG 306
Valid rim size	7.00 I x 12 H2
Rim connection	5/67/112
Bolt hole design	E12
Offset (mm)	+10
Rim colour	Silver
Load capacity complete wheel [kg]	580
Speed complete wheel [km/h]	30



Technical Informations

Assembly Item no. Tyres	• 15710480
LI / SI / PR	89 A6, 6 PR
Load capacity 1 [kg]	580
Speed 1 [km/h].	30
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	15,58
ECE regulation number	ECE 106
Section width (mm)	210
Stat. radius (SLR) [mm]	258
Rolling circumference [mm].	1709

Tread depth (mm)	10,0
E-Ready	No
Assembly Item no. Rim	• 30810270
Load capacity of rim 1 [kg]	900
Speed Rims 1 [km/h]	140
Load capacity of rim 2 [kg]	950
Maximum speed [km/h].	30
Maximum air pressure [bar].	2,30
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve

Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade