

## WHEELS

Product group	Wheels
Item number	59910058
Valid wheel size	26 x 12.00 - 12
Brand	BKT
Tread pattern	LG 306
Valid rim size	10.50 I x 12 H2
Rim connection	4/60/100
Bolt hole design	A1
Offset (mm)	-70
Rim colour	Silver
Load capacity complete wheel [kg]	1120
Speed complete wheel [km/h]	30



## Technical Informations

Assembly Item no. Tyres	• 15710500
LI / SI / PR	116 A3 / 112 A6, 8 PR
Load capacity 1 [kg]	1250
Speed 1 [km/h].	15
Load capacity 2 [kg]	1120
Speed 2 [km/h].	30
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	33,67
ECE regulation number	ECE 106
Section width (mm)	310

Stat. radius (SLR) [mm]	283
Rolling circumference [mm].	1856
Tread depth (mm)	10,0
E-Ready	No
Assembly Item no. Rim	• 30810301
Load capacity of rim 1 [kg]	800
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	30
Maximum air pressure [bar].	3,00
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	4
Bolt hole design EUWA	B14 ES 28
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	60
Bolt hole circle diameter [mm]	100
Valve seat	External Valve
Valve hole diameter [mm]	11.3

---

Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade