

WHEELS

| | |
|-----------------------------------|-----------------|
| Product group | Wheels |
| Item number | 59910091 |
| Valid wheel size | 26 x 12.00 - 12 |
| Brand | BKT |
| Tread pattern | TR 315 |
| Valid rim size | 10.50 I x 12 H2 |
| Rim connection | 5/94/140 |
| Bolt hole design | A1 |
| Offset (mm) | -30 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 1450 |
| Speed complete wheel [km/h] | 15 |



Technical Informations

| | |
|-----------------------------|---------------|
| Assembly Item no. Tyres | • 15710520 |
| LI / SI / PR | 121 A6, 12 PR |
| Load capacity 1 [kg] | 1450 |
| Speed 1 [km/h]. | 30 |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 31,26 |
| ECE regulation number | ECE 106 |
| Section width (mm) | 308 |
| Stat. radius (SLR) [mm] | 289 |
| Rolling circumference [mm]. | 1905 |

| | |
|--------------------------------|----------------|
| Tread depth (mm) | 18,5 |
| Number of lugs | 20x2 |
| E-Ready | No |
| Assembly Item no. Rim | • 31610061 |
| Load capacity of rim 1 [kg] | 1600 |
| Speed Rims 1 [km/h] | 15 |
| Maximum speed [km/h]. | 15 |
| Maximum air pressure [bar]. | 4,50 |
| Type of drive | Towed axle |
| Hump | H2 |
| Valve protection | VS H |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 5 |
| Bolt hole design EUWA | B14 ES 28 |
| Bolt hole diameter [mm] | 18 |
| Countersinking | Sphere |
| hub hole diameter [mm]. | 94 |
| Bolt hole circle diameter [mm] | 140 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 11.3 |
| Preassembled valve | No |

| | |
|-------------------|-------------|
| Valve design | Metal valve |
| Valve length [mm] | 42.0 |
| Valve angle [°] | gerade |