

WHEELS

| | |
|-----------------------------------|-----------------|
| Product group | Wheels |
| Item number | 59910095 |
| Valid wheel size | 320 / 55 - 12 |
| Brand | Vredestein |
| Tread pattern | GREENTRAX |
| Valid rim size | 10.50 I x 12 H2 |
| Rim connection | 5/94/140 |
| Offset (mm) | +26.5 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 1250 |
| Speed complete wheel [km/h] | 40 |



Technical Informations

| | |
|-----------------------------|------------|
| Assembly Item no. Tyres | • 14811285 |
| LI / SI / PR | 116 A8 |
| Load capacity 1 [kg] | 1250 |
| Speed 1 [km/h]. | 40 |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 26,12 |
| ECE regulation number | ECE 106 |
| Section width (mm) | 320 |
| Stat. radius (SLR) [mm] | 300 |
| Rolling circumference [mm]. | 1965 |

| | |
|--------------------------------|-------------------------------|
| E-Ready | No |
| Assembly Item no. Rim | • 39600382 |
| Load capacity of rim 1 [kg] | 900 |
| Speed Rims 1 [km/h] | 40 |
| Maximum speed [km/h]. | 40 |
| Maximum air pressure [bar]. | 2,40 |
| Type of drive | Angetriebene & gezogene Achse |
| Hump | H2 |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 5 |
| Bolt hole diameter [mm] | 16 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R14 |
| hub hole diameter [mm]. | 94 |
| Bolt hole circle diameter [mm] | 140 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 11.3 |
| Preassembled valve | No |
| Valve design | Rubber valve |
| Valve designation ETRTO | V2.03.1 |
| Valve length [mm] | 43.0 |

| |
|-----------------|
| Valve angle [°] |
|-----------------|

| |
|--------|
| gerade |
|--------|
