

WHEELS

Product group	Wheels
Item number	59910547
Valid wheel size	27 x 10 - 15.3
Brand	BKT
Tread pattern	AS 504
Valid rim size	9.00 x 15.3
Rim connection	6/161/205
Bolt hole design	E2
Offset (mm)	+20
Rim colour	Silver
Load capacity complete wheel [kg]	975
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15710547
LI / SI / PR	95 A8 / 107 A8, 8 PR
Load capacity 1 [kg]	690
Speed 1 [km/h].	40
Load capacity 2 [kg]	975
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	35,99
ECE regulation number	ECE 106
Section width (mm)	260

Stat. radius (SLR) [mm]	317
Rolling circumference [mm].	2071
Tread depth (mm)	23,0
E-Ready	No
Assembly Item no. Rim	• 32010166
Load capacity of rim 1 [kg]	2360
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,10
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7

Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade