

WHEELS

Product group	Wheels
Item number	59911060
Valid wheel size	7.00 - 12
Brand	BKT
Tread pattern	AS 504
Valid rim size	5 JA x 12
Rim connection	5/67/112
Bolt hole design	B1
Offset (mm)	+40
Rim colour	Silver
Load capacity complete wheel [kg]	560
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15711300
LI / SI / PR	75 A8 / 88 A8, 4 PR
Load capacity 1 [kg]	387
Speed 1 [km/h].	40
Load capacity 2 [kg]	560
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	19,64
ECE regulation number	ECE 106
Section width (mm)	187

Stat. radius (SLR) [mm]	300
Rolling circumference [mm].	2001
Tread depth (mm)	19,0
Number of lugs	22x2
E-Ready	No
Assembly Item no. Rim	• 30820101
Load capacity of rim 1 [kg]	990
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,40
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole design EUWA	B14 DS 28
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112

Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade