

WHEELS

Product group	Wheels
Item number	59911075
Valid wheel size	4.00 - 12
Brand	BKT
Tread pattern	TF 9090
Valid rim size	4 J x 12
Rim connection	4/57/100
Rim colour	Silver
Load capacity complete wheel [kg]	315
Speed complete wheel [km/h]	30
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15721010
LI / SI / PR	68 A6 / 60 A8, 6 PR
Load capacity 1 [kg]	315
Speed 1 [km/h].	30
Load capacity 2 [kg]	250
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	10,19
ECE regulation number	ECE 106
Section width (mm)	112

Stat. radius (SLR) [mm]	255
Rolling circumference [mm].	1573
Tread depth (mm)	11,0
E-Ready	No
Assembly Item no. Rim	• 30820090
Load capacity of rim 1 [kg]	600
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	5,10
Number of bolt holes	4
hub hole diameter [mm].	57
Bolt hole circle diameter [mm]	100
Bolt hole diameter [mm]	15.5
Countersinking	Sphere
Spherical countersink [mm].	R12
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	11.3

Preassembled valve	No
TPMS-kompatibles Ventil	No
