

WHEELS

Product group	Wheels
Item number	59911097
Valid wheel size	7.00 - 12
Brand	ВКТ
Tread pattern	Power Trax HD Forklift
Valid rim size	5.00 S - 12
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver





Technical Informations

Assembly Item no. Tyres •	15771103
LI / SI / PR	14 Pr
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	37,42
ECE regulation number	not necessary
Section width (mm)	205
Tread depth (mm)	18,0
E-Ready	No
Assembly Item no. Rim •	31610041
Load capacity of rim 1 [kg]	2120

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Speed Rims 1 [km/h] 25 Load capacity of rim 2 [kg] 1900 Speed Rims 2 [km/h] 40 Maximum air pressure [bar]. 9,00 Type of drive Angetriebene & gezogene Achse Hump kein Hump Single / multi-part mehrteilig Quantity multi-piece two-part Rim material steel RAL RAL9006 Cavity Sealed No	
Speed Rims 2 [km/h] 40 Maximum air pressure [bar]. 9,00 Type of drive Angetriebene & gezogene Achse Hump kein Hump Single / multi-part mehrteilig Quantity multi-piece two-part Rim material steel RAL RAL9006	
Maximum air pressure [bar]. 9,00 Type of drive Angetriebene & gezogene Achse Hump kein Hump Single / multi-part mehrteilig Quantity multi-piece two-part Rim material steel RAL RAL9006	
Type of drive Angetriebene & gezogene Achse Hump kein Hump Single / multi-part mehrteilig Quantity multi-piece two-part Rim material steel RAL RAL9006	
Hump kein Hump Single / multi-part mehrteilig Quantity multi-piece two-part Rim material steel RAL RAL9006	
Single / multi-part mehrteilig Quantity multi-piece two-part Rim material steel RAL RAL9006	
Quantity multi-piece two-part Rim material steel RAL RAL9006	
Rim material steel RAL RAL9006	
RAL RAL9006	
Cavity Sealed No	
Knurling without knurling	
Ventilation holes No	
Verschweißung beidseitig No	
Rim centering BC	
Number of bolt holes 6	
Bolt hole diameter [mm] 21.5	
Countersinking Sphere	
Spherical countersink [mm]. R16	
hub hole diameter [mm]. 161	
Bolt hole circle diameter [mm] 205	
Valve seat External Valve	
Preassembled valve No	