Bohnenkamp Moving Professionals

15.11.2024

WHEELS

Product group Wheels	
Item number	59911102
Valid wheel size	11.0 / 65 - 12
Brand	ВКТ
Tread pattern	AS 504
Valid rim size	7.00 x 12
Rim colour	Silver
Load capacity complete wheel [kg]	825
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres •	15711285
LI / SI / PR	101 A8 / 114 A8, 8 PR
Load capacity 1 [kg]	825
Speed 1 [km/h].	40
Load capacity 2 [kg]	1180
Speed 2 [km/h].	40
Direction	Right
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	30,69
ECE regulation number	ECE 106

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

15.11.2024

Sector with the sector with th		
Rolling circumference [mm]2022Tread depth (mm)20.0E-ReadyNoAssembly tem no. Rim30810262Load capacity of rim [fw]70Speed Rims 1 [km/h]40Maximum speed [km/h]0Maximum air pressure [bm]20.0Type of drive100Bingle / multi-part8inBillSingle / multi-part8inBillRim material8inBillRin materialNoVarial Speed RimonNoVarial Speed RimonNoChristian Decimal Speed RimonNoRin MaterialNoRin Materia	Section width (mm)	273
Tead depth (mm)2.0E-ReadyNoAssembly tem on Rim30810262Lad capacity of rim [km]9/0Speed Rims 1 (km)0Maximum speed (km/h)0Maximum ar pressure [km]0Jop of drive100Type of drive100Bingle / multi-part100Bingle / multi-part100 <t< th=""><th>Stat. radius (SLR) [mm]</th><th>321</th></t<>	Stat. radius (SLR) [mm]	321
E-RadyNoAssembly them o. Rim30810262Load capacity of rim 1(a)970Speed Rim 1(a)40Maximum speed [km/h]40Maximum apressure (b)309Type of drive100Mode axerowed axeBingle / multi-partineliligRim aterial80Ruft (b)NoCaty SealedNoVariange (b)NoVariange (b)NoVariange (b)NoStarbing (b)NoStarbing (b)NoVariange (b)NoVariange (b)SiNoSiStarbing (b)SiVariange (b)NoVariange (b)NoStarbing (b)<	Rolling circumference [mm].	2072
Assembly item no. Rim 30810262 Load capacity of rim 1(kg) 970 Speed Rims 1[km/h] 40 Maximum speed [km/h] 40 Maximum speed [km/h] 200 Single / multi-part einelig Single / multi-part einelig Rith material seel RAL RA.9006 Varbitation holes No Varbitation holes No Valve seat Sol Valve seat Sol Valve design No Valve design No Valve design Sol Valve design <th>Tread depth (mm)</th> <th>22,0</th>	Tread depth (mm)	22,0
Load capacity of rim 1 (kg) initial initinitial initial initial initial initial initinitinitia	E-Ready	No
Speed Rins 1 [km/h] 40 Maximum speed [km/h]. 40 Maximum air pressure [bas] 290 Type of drive Towed axle Binge / multi-part eineling Single / multi-part eineling Ramaerial seel Ratur RAL9006 Variation holes No Variation holes No Vare seat External Valve Vare seation Single / multi-part Vare seation No Vare seation No Vare seation Single / multi-part Vare seation No Vare seation No Vare seation Single / multi-part Vare seation No Vare seation Single / multi-part Vare seation Single / multi-part Vare seatin [multi-part Single / multi-part	Assembly Item no. Rim	30810262
Maximum speed [km/h] 40 Maximum air pressure [ba] 5.00 Type of drive Fowed xale Type of drive Fowed xale Hump Kein Hump Single / multi-part einelitig Rim material Seel Rat RAL9006 Varity Sealed No Varity Sealed No Varchweißung beidsetig No Varchweißung beidsetig No Vare seat Scienau Valve Varkende diameter [mm] Si.7 Varke seatig No <	Load capacity of rim 1 [kg]	970
Maximum air pressure [bar] 2,90 Type of drive Towed axle Hump kein Hump Single / multi-part einteilig Rin material steel RAL RAL9006 Vortilation holes No Varschweißung beidseitig No Varschweißung beidseitig No Preasembled valve No TPMS-kompatibles Ventil No Valve design No Valve angle [*] Sa Valve angle [*] Back	Speed Rims 1 [km/h]	40
Type of driveTowed axleType of driveTowed axleHumpkein HumpSingle / multi-parteinteiligRin materialseelRALSoloCavity SealedNoVertilation holesNoVarschweißung beidseitigNoValve seatExternal ValvePreasembled valveNoTymeS-tompatibles VertilNoValve designNoValve designSelValve designSelValve angle [°]SelSelSelValve angle [°]SelBackBack	Maximum speed [km/h].	40
Hump kein Hump Single / multi-part einteilig Rin material steel RAL RAL9006 Cavity Sealed No Ventilation holes No Varschweißung beidseitig No Valve seat External Valve Preasembled valve No TPMS-kompatibles Ventil No Valve design No Valve long fig Sa Valve note of ing Sa Valve design No Valve design Sa Valve design Ba Valve design Sa	Maximum air pressure [bar].	2,90
Single / multi-parteinteiligSingle / multi-parteinteiligRalstelRALRAL9006Cavity SealedNoVentilation holesNoVarschweißung beidseitigNoValve seatExternal ValveValve hole diameter [mm]15.7Preasembled valveNoValve designNoValve designSider valveValve long [m]38Valve angle [m]Bick	Type of drive	Towed axle
Rin materialsteelRALRAL9006Cavity SealedNoVentilation holesNoVerschweißung beidseitigNoValve seatExternal ValveValve hole diameter [mm]15.7Preasembled valveNoValve designNoValve designSuber valveValve length [mm]3State length [mm]Biack	Hump	kein Hump
RAL AB006 cavity Sealed No Vertilation holes No Varson Marcine Scienal Value Varson Marcine Scienal Value Varson Marcine No Varson Marcine Science	Single / multi-part	einteilig
Cavity SealedNoVentilation holesNoVerschweißung beidseitigNoValve seatExternal ValveValve hole diameter [mm]15.7Preassembled valveNoTPMS-kompatibles VentilNoValve designRubber valveValve length [mm]38Calve angle [°]Bick	Rim material	steel
Ventilation holesNoVerschweißung beidseitigNoValve seatExternal ValveValve hole diameter [mm]15.7Preassembled valveNoTPMS-kompatibles VentilNoValve designRubber valveValve length [mm]38Calve angle [°]geradeBackBack	RAL	RAL9006
Varschweißung beidseitig No Valve seat External Valve Valve hole diameter [mm] 15.7 Preassembled valve No TPMS-kompatibles Ventil No Valve design No Valve length [mm] 38 Valve angle [°] gerade Black Modername	Cavity Sealed	No
Valve seat External Valve Valve hole diameter [mm] 15.7 Preassembled valve No TPMS-kompatibles Ventil No Valve design No Valve length [mm] 38 Valve angle [°] gerade Back Back	Ventilation holes	No
Valve hole diameter [mm] 15.7 Preassembled valve No TPMS-kompatibles Ventil No Valve design Rubber valve Valve length [mm] 38 Valve angle [°] gerade Black No	Verschweißung beidseitig	No
Preassembled valve No TPMS-kompatibles Ventil No Valve design Rubber valve Valve length [mm] 38 Valve angle [°] gerade Black Black	Valve seat	External Valve
TPMS-kompatibles Ventil No Valve design Rubber valve Valve length [mm] 38 Valve angle [°] gerade Black Black	Valve hole diameter [mm]	15.7
Valve design Rubber valve Valve length [mm] 38 Valve angle [°] gerade Black Black	Preassembled valve	No
Valve length [mm] 38 Valve angle [°] gerade Colour of cap Black	TPMS-kompatibles Ventil	No
Valve angle [°] gerade Colour of cap Black	Valve design	Rubber valve
Colour of cap Black	Valve length [mm]	38
	Valve angle [°]	gerade
Valve cap Material Plastic	Colour of cap	Black
	Valve cap Material	Plastic

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.