

## WHEELS

Product group	Wheels
Item number	59911112
Valid wheel size	10.0 / 80 - 12
Brand	BKT
Tread pattern	AW 702
Valid rim size	7.00 I x 12 H2
Rim connection	5/67/112
Bolt hole design	E12
Offset (mm)	+10
Rim colour	Silver
Load capacity complete wheel [kg]	1000
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15711540
LI / SI / PR	121 A8, 10 PR
Load capacity 1 [kg]	1450
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	24,17
ECE regulation number	ECE 106
Section width (mm)	264
Stat. radius (SLR) [mm]	317
Rolling circumference [mm].	2144

Tread depth (mm)	10,0
E-Ready	No
Assembly Item no. Rim	• 30810270
Load capacity of rim 1 [kg]	900
Speed Rims 1 [km/h]	140
Load capacity of rim 2 [kg]	950
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,90
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No