

WHEELS

Product group	Wheels
Item number	59911113
Valid wheel size	10.0 / 80 - 12
Brand	BKT
Tread pattern	AW 702
Valid rim size	7.00 x 12
Rim connection	5/94/140
Bolt hole design	E1
Rim colour	Silver
Load capacity complete wheel [kg]	1450
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15711540
LI / SI / PR	121 A8, 10 PR
Load capacity 1 [kg]	1450
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	22,92
ECE regulation number	ECE 106
Section width (mm)	264
Stat. radius (SLR) [mm]	317
Rolling circumference [mm].	2144

Tread depth (mm)	10,0
E-Ready	No
Assembly Item no. Rim	• 30810265
Load capacity of rim 1 [kg]	1330
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	500
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,90
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	94
Bolt hole circle diameter [mm]	140
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No

Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade