

WHEELS

Product group	Wheels
Item number	59911114
Valid wheel size	10.0 / 80 - 12
Brand	ВКТ
Tread pattern	Rib Implement (A)
LI / SI / PR	117 A6 / 110 A8, 6 PR
TL/TT	TL
Hub design	End cap assembly
Type of bearing	Without bearing
Shaft diameter [mm].	40.5
Mounting length [mm]	125
Hub length [mm]	125
Rim colour	Silver
Load capacity complete wheel [kg]	970
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres •	15711545
LI / SI / PR	117 A6 / 110 A8, 6 PR
TL/TT	TL
Brand	BKT
Tread pattern	Rib Implement (A)
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Maximum air pressure [bar].	2,30
Section width (mm)	264
Stat. radius (SLR) [mm]	329
Rolling circumference [mm].	2186
Tread depth (mm)	18,0
Assembly Item no. Rim •	30810262
Valid rim size	7.00 x 12
Load capacity of rim 1 [kg]	970
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Verschweißung beidseitig	No
Offset hub	No
Additional socket required	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0