

WHEELS

Product group	Wheels
Item number	59911118
Valid wheel size	7.00 - 12
Brand	BKT
Tread pattern	AS 504
Valid rim size	7.00 x 12
Rim colour	Silver
Load capacity complete wheel [kg]	487
Speed complete wheel [km/h]	40





Technical Informations

Assembly Item no. Tyres	15711305
LI / SI / PR	83 A8 / 95 A8, 6 PR
Load capacity 1 [kg]	487
Speed 1 [km/h].	40
Load capacity 2 [kg]	690
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	24,25
ECE regulation number	ECE 106
Section width (mm)	187

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Stat. radius (SLR) [mm]	300
Rolling circumference [mm].	2001
Tread depth (mm)	19,0
Number of lugs	22x2
E-Ready	No
Assembly Item no. Rim •	30810262
Load capacity of rim 1 [kg]	970
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,40
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No