

WHEELS

Product group	Wheels
Item number	59911170
Valid wheel size	7.5 L - 15
Brand	BKT
Tread pattern	AS 504
Valid rim size	6 J x 15 H2
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	800
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15711690
LI / SI / PR	100 A8 / 113 A8, 8 PR
Load capacity 1 [kg]	800
Speed 1 [km/h].	40
Load capacity 2 [kg]	1150
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	27,67
ECE regulation number	ECE 106

Section width (mm)	210
Stat. radius (SLR) [mm]	354
Rolling circumference [mm].	2280
Tread depth (mm)	25,0
E-Ready	No
Assembly Item no. Rim	• 31610095
Load capacity of rim 1 [kg]	1285
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,70
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	11.3

Preassembled valve	No
TPMS-kompatibles Ventil	No