

WHEELS

Product group	Wheels
Item number	59911206
Valid wheel size	10.5 / 80 - 18
Brand	Alliance
Tread pattern	320 Value Plus
Valid rim size	9 x 18
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	2180
Speed complete wheel [km/h]	30





Technical Informations

Assembly Item no. Tyres	15212311
LI / SI / PR	135 A6 / 131 A8, 10 PR
Load capacity 1 [kg]	2180
Speed 1 [km/h].	30
Load capacity 2 [kg]	1950
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	44,86
ECE regulation number	ECE 106
Section width (mm)	274

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Stat. radius (SLR) [mm]	390
Rolling circumference [mm].	2620
Tread depth (mm)	9,0
E-Ready	No
Assembly Item no. Rim •	32010145
Load capacity of rim 1 [kg]	3250
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,70
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.





Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade