

WHEELS

Product group	Wheels
Item number	59911208
Valid wheel size	12.5 / 80 - 18
Brand	Alliance
Tread pattern	320 Value Plus
Valid rim size	11 x 18
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	-35
Rim colour	Silver
Load capacity complete wheel [kg]	3550
Speed complete wheel [km/h]	30



Technical Informations

Assembly Item no. Tyres	• 15212337
LI / SI / PR	152 A6 / 148 A8, 16 PR
Load capacity 1 [kg]	3550
Speed 1 [km/h].	30
Load capacity 2 [kg]	3150
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	69,60
ECE regulation number	ECE 106
Section width (mm)	308

Stat. radius (SLR) [mm]	422
Rolling circumference [mm].	2870
Tread depth (mm)	9,0
E-Ready	No
Assembly Item no. Rim	• 31210155
Load capacity of rim 1 [kg]	3250
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	1800
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,90
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve

Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade