

WHEELS

Product group	Wheels
Item number	59911209
Valid wheel size	12.5 / 80 - 18
Brand	Alliance
Tread pattern	320 Value Plus
Valid rim size	11 x 18
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	3550
Speed complete wheel [km/h]	30



Technical Informations

Assembly Item no. Tyres	• 15212337
LI / SI / PR	152 A6 / 148 A8, 16 PR
Load capacity 1 [kg]	3550
Speed 1 [km/h].	30
Load capacity 2 [kg]	3150
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	65,10
ECE regulation number	ECE 106
Section width (mm)	308

Stat. radius (SLR) [mm]	422
Rolling circumference [mm].	2870
Tread depth (mm)	9,0
E-Ready	No
Assembly Item no. Rim	• 32010230
Load capacity of rim 1 [kg]	4125
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3000
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,90
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade