

WHEELS

Product group	Wheels
Item number	59911293
Valid wheel size	10.5 / 80 - 18
Brand	BKT
Tread pattern	AW 702
Valid rim size	9 x 18
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	2360
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15711877
LI / SI / PR	138 A8, 14 PR
Load capacity 1 [kg]	2360
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	49,56
ECE regulation number	ECE 106
Section width (mm)	275
Stat. radius (SLR) [mm]	395
Speed Radius Index (SRI)	425

Rolling circumference [mm].	2593
Tread depth (mm)	11,0
E-Ready	No
Assembly Item no. Rim	• 32010145
Load capacity of rim 1 [kg]	3250
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	5,10
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve

Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade