

## WHEELS

|                                   |                  |
|-----------------------------------|------------------|
| Product group                     | Wheels           |
| Item number                       | 59911320         |
| Valid wheel size                  | 10.0 / 75 - 15.3 |
| Brand                             | BKT              |
| Tread pattern                     | AW 702           |
| Valid rim size                    | 9.00 x 15.3      |
| Rim connection                    | 6/161/205        |
| Bolt hole design                  | E2               |
| Offset (mm)                       | -5               |
| Rim colour                        | Silver           |
| Load capacity complete wheel [kg] | 1550             |
| Speed complete wheel [km/h]       | 40               |



## Technical Informations

|                             |               |
|-----------------------------|---------------|
| Assembly Item no. Tyres     | • 15711730    |
| LI / SI / PR                | 123 A8, 10 PR |
| Load capacity 1 [kg]        | 1550          |
| Speed 1 [km/h].             | 40            |
| Antistatic                  | No            |
| Tyre colour                 | Black         |
| Nettogewicht [kg] (gültig)  | 29,68         |
| ECE regulation number       | ECE 106       |
| Section width (mm)          | 274           |
| Stat. radius (SLR) [mm]     | 343           |
| Rolling circumference [mm]. | 2227          |

|                                |                               |
|--------------------------------|-------------------------------|
| Tread depth (mm)               | 10,5                          |
| E-Ready                        | No                            |
| Assembly Item no. Rim          | • 31810195                    |
| Load capacity of rim 1 [kg]    | 2800                          |
| Speed Rims 1 [km/h]            | 25                            |
| Load capacity of rim 2 [kg]    | 2650                          |
| Speed Rims 2 [km/h]            | 40                            |
| Maximum speed [km/h].          | 40                            |
| Maximum air pressure [bar].    | 3,90                          |
| Type of drive                  | Angetriebene & gezogene Achse |
| Hump                           | kein Hump                     |
| Single / multi-part            | einteilig                     |
| Rim material                   | steel                         |
| RAL                            | RAL9006                       |
| Cavity Sealed                  | No                            |
| Knurling                       | without knurling              |
| Ventilation holes              | No                            |
| Verschweißung beidseitig       | No                            |
| Rim centering                  | BC                            |
| Number of bolt holes           | 6                             |
| Bolt hole diameter [mm]        | 21.5                          |
| Countersinking                 | Sphere                        |
| Spherical countersink [mm].    | R16                           |
| hub hole diameter [mm].        | 161                           |
| Bolt hole circle diameter [mm] | 205                           |
| Valve seat                     | External Valve                |
| Valve hole diameter [mm]       | 15.7                          |

---

|                    |
|--------------------|
| Preassembled valve |
|--------------------|

|    |
|----|
| No |
|----|