

WHEELS

Product group	Wheels
Item number	59911461
Valid wheel size	10.0 / 75 - 15.3
Brand	BKT
Tread pattern	AW 702
Valid rim size	9.00 x 15.3
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	-40
Rim colour	Silver
Load capacity complete wheel [kg]	1900
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15711734
LI / SI / PR	130 A8, 14 PR
Load capacity 1 [kg]	1900
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	32,30
ECE regulation number	ECE 106
Section width (mm)	274
Stat. radius (SLR) [mm]	343
Rolling circumference [mm].	2227

Tread depth (mm)	11,0
E-Ready	No
Assembly Item no. Rim	• 30810181
Load capacity of rim 1 [kg]	2700
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	2180
Speed Rims 2 [km/h]	60
Maximum speed [km/h].	40
Maximum air pressure [bar].	5,50
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7

Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade