

WHEELS

Product group	Wheels
Item number	59911464
Valid wheel size	10.0 / 75 - 15.3
Brand	BKT
Tread pattern	AW 702
Valid rim size	9.00 x 15.3
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-25
Rim colour	Red
Load capacity complete wheel [kg]	2360
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15711738
LI / SI / PR	135 A8, 18 PR
Load capacity 1 [kg]	2180
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	33,85
ECE regulation number	ECE 106
Section width (mm)	274

Stat. radius (SLR) [mm]	351
Rolling circumference [mm].	2227
Tread depth (mm)	10,5
E-Ready	No
Assembly Item no. Rim	• 33060021
Load capacity of rim 1 [kg]	3400
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2850
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	7,10
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL3000
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve

Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade