

WHEELS

Product group	Wheels
Item number	59911467
Valid wheel size	12.0 / 75 - 18
Brand	Alliance
Tread pattern	317 (Spacer)
Valid rim size	9 x 18
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-30
Rim colour	Silver
Load capacity complete wheel [kg]	2180
Speed complete wheel [km/h]	40





Technical Informations

Assembly Item no. Tyres	15212315
LI / SI / PR	139 A6 / 135 A8, 12 PR
Load capacity 1 [kg]	2430
Speed 1 [km/h].	30
Load capacity 2 [kg]	2180
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	60,46
ECE regulation number	ECE 106
Section width (mm)	299

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Stat. radius (SLR) [mm]	411
Rolling circumference [mm].	2690
Tread depth (mm)	18,0
Tyre capacity 75% [ltr.]	127
E-Ready	No
Assembly Item no. Rim •	32010138
Load capacity of rim 1 [kg]	3250
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.





Valve hole diameter [mm]	15.7
Preassembled valve	No